

**SIVIT SRL**

Via Centallo, 57

10156 TORINO - ITALY

Tel. 0039 011 2730033 – Fax 0039 011 2735617

[www.sivit.it](http://www.sivit.it)

[info@sivit.it](mailto:info@sivit.it)

Rev. A del 11/05 - Sigla

**WALKABLE WATERPROOFING**

- ◆ Concrete surfaces must be solid, dry (new concrete must be seasoned), levelled, absorbent, free from dust and other substances.

Treat the surface by abrasion with the aim to open the porosity of concrete.

- ◆ Apply a coat of waterborne two-pack epoxy system **PAVIWATER T/68 A+B** diluted 1 : 1,5 in water for a consumption of 0,100 kg/m<sup>2</sup> of A+B.
- ◆ Make a reinforced resinous covering impregnating a crossed glass fiber (MAT 300) with **BASE LP** diluted with **SOLVENTE UNI** ( apply a coat of **BASE LP** on surface then lay the MAT on surface then impregnate the MAT with **BASE LP** diluted with 10% of **SOLVENTE UNI**).
- ◆ Apply two coats of a mixture 1 : 1 of **BASE LP** and **PASTA LP** for a total consumption of 2 Kg/m<sup>2</sup>.
- ◆ Protect the surface from UV rays by a coat of **FINITURA LP colorata A+B** for a consumption of 0,150 Kg/m<sup>2</sup>.